

	eDRAULIC Cutter			EN
	S 120 e 90-20-10			
	Technical Data			
Non-metric dimensions are for reference only.				
Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	465 x 81,6 x 127,3 18.3 x 3.21 x 5.08	mm in.	closed; w/o battery
Weight		3,7 8.16	kg lbs.	incl. hydraulic fluid, w/o battery
Weight battery		0,4 0.88	kg lbs.	2 Ah
Current consumption		4,1 20	A A	idle mode max. load
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Opening / closing time	>	2	s	w/o load
Cutting performance		Ø22 Ø0.87	mm in.	acc. to EN 13204 / NFPA 1960
Opening width at tips		52,3 2.06	mm in.	at tips
Operating pressure		70 10,000	MPa psi	
Sound power level		79	dB(A)	acc. to EN 13204
EN 13204 Cutting performance		1E-2C-3B		
Protection class DIN EN 60529:2014-09		IP 44		
Note: Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
LUKAS Hydraulik GmbH Weinstraße 39 • D-91058 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394				